Inline-P3



DIN RAIL

Fieldbus

Embedded OS

- **Fanless**
  without fan up to PIII 933 MHz
- **Fieldbus on board**
  Can open, Device Net or Profibus
- **High Scalable**
  3 x PC/104 extension

Product Overview

Fanless DIN Rail mount PC, Fieldbus inclusive with Processors up to PIII 933MHz, high shock and vibration as well Temperature Specification. Inline-P3 is the first choice as peripheral IPC in rough Industrial environmen.
If it is fanless it is Inline.

Technical Data

Expansion Slots
3x PC/104
Drivers
HDD optional
OS
Windows XP Embedded
Windows CE.net
Linux Embedded
Power Supply
24 VDC +/- 20%
Mounting
DIN RAIL, optional Wall Mount
Protection class
IP 20 (frontside) according EN 60529
Temperature operating
0° to +50°C
Non operating
-25° to +70°C
Humidity
5-95% (non condensing)
Dimensions (BxHxT)
270mm x 183mm x 77,4mm
Warranty
24 month

Processor
200/300 MHz Geode GX1
Celeron 400 MHz bis 650 MHz
Pentium III 933 MHz
Memory
up to 256 MB PC 133
up to 512 MB mit Pentium III
Compact Flash
up to 1 GB
I/Os
2x USB
2x PS/2
1x LPT
1x LAN 10/100 Base-TX
3x RS 232
1x CRT
Fieldbus
CanOpen, DeviceNet, Profibus oder MDI

(*) see manual for details

Corporate Offices

Europe, Middle East & Africa
Oskar-von-Miller-Straße 1
85386 Eching/Munich - Germany

Tel.: +49 (0)8165/ 77 0
Fax: +49 (0)8165/ 77 279

sales@kontron.com

US/ Canada
6260 Sequence Drive
San Diego, CA 92121-4371

Tel.: (858) 677-0877
Fax: (858) 677-0898

sales@us.kontron.com

Asia Pacific
5F-1, 341, Sec 4, Chung Hsiao E.
Rd, Taipei, Taiwan

Tel: +886 2 2781 5791
Fax: +886 2 2741 7379

sales@kontron.com.tw

#PxV206 - M#030925rf
All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. All brand or product names are trademarks or registered trademarks of their respective owners.

kontron
... always a Jump ahead!